

f8

An 8-Bit architecture based on lessons learned from SDCC and
the architectures it supports

Philipp Klaus Krause

2022-07-08

8-Bit architectures

- In between low-end (4-bit) and high-end (32- and 64-bit microcontrollers).
- Typically programmed in C
- Devices cost about 1¢ to 1 €
- Data memory typically in the range of a few B to a few KB
- Program memory typically a few KB
- Market dominated by proprietary architectures, and ancient architectures implemented by many vendors

The Small Device C Compiler

- Free C compiler (ANSI C89, ISO C99, ISO C11, ISO C2X)
- Freestanding implementation or part of a hosted implementation
- Supporting tools (assembler, linker, simulator, ...)
- Works on many host systems (GNU/Linux, Windows, macOS, Hurd, OpenBSD, FreeBSD, ...)
- Targets various 8-bit architectures (MCS-51, DS80C390, Z80, Z180, eZ80 in Z80 mode, Rabbit 2000, Rabbit 2000A, Rabbit 3000A, SM83, TLCS-90, HC08, S08, STM8, pdk14, pdk15, pdk13, 6502, PIC14, PIC16)
- Has some unusual optimizations that make sense for these targets (in particular in register allocation)
- Users: μ C programmers, and retrocomputing/-gaming developers

Lessons learned - big picture

- An efficient stackpointer-relative addressing is essential for reentrant functions
- A unified address space is essential for efficient pointer access
- Registers help
- Hardware multithreading can replace peripheral hardware, but it needs good support for atomics, and thread-local storage
- Irregular architectures can be very efficient with tree-decomposition-based register allocation
- A good mixture of 8-bit and 16-bit operations helps
- Pointers should be 16 bits

Lessons learned - details

- Zero-page, etc addressing isn't useful if we have efficient stackpointer-relative addressing
- A index-pointer-relative read instruction for both 8 and 16 bits is important
- Prefix bytes can be a good way to allow more operands (e.g. registers)
- Hardware $8 \times 8 \rightarrow 16$ multiplication helps
- Division is rare
- Multiply-and-add helps speeds up wider multiplications
- BCD support provides cheap printf without need for hardware division
- Good shift and rotate support helps

Where do we get

- 8/16 bit
- Irregular CISC
- The core becomes bigger than for RISC, but we save so much on code memory that it is worth it
- Approximately 30% lower code size than stm8 - in current very early experimental SDCC backend